

Billing Performance (BI)

Function:		
BI-1 Timeliness of Daily Usage Feed		
Definition:		
<p>The number of business days from the creation of the message to the date that the usage information is made available to the CLEC on the Daily Usage Feed (DUF). Measured in percentage of usage records transmitted within four (4) business days. One report covers both UNE and Resale. For CLECs requesting this service, usage records will be provided to CLECs each business day. The usage process starts with collection of usage information from the switch. Most offices have this information teleprocessed to the data center. Not all offices poll usage every business day. Weekend and holiday usage is captured on the next business day. Usage for all CLECs is collected at the same time as VZ's.</p>		
Note:		
<ul style="list-style-type: none"> Verizon New York monitors the level of service order errors with the potential of delaying usage feeds; Verizon New York monitors the timeliness of the usage feed to the process on a daily basis; and <p>Verizon New York offers its CLEC customers the option of receiving EMI usage feeds through the Network Data Mover (NDM) process to increase the timeliness of delivery.</p>		
Exclusions:		
Verizon Test Orders		
Formula:		
(Total usage records in "y" business days divided by the total records on file) multiplied by 100		
Note: y = 4		
Performance Standard:		
Process is Designed at parity with Retail		
BI-1-02: 95% in Four (4) Business Days		
Report Dimensions		
Company:		Geography:
<ul style="list-style-type: none"> CLEC Aggregate CLEC Specific 		<ul style="list-style-type: none"> New York
Sub-Metrics		
BI-1-01	Metric Not in Use in Verizon North	
BI-1-02	% DUF in four (4) Business Days	
Calculation	Numerator	Denominator
	Number of usage records on daily usage feed tapes processed during month, where the difference between current date and call date is four (4) days or less.	Number of Usage Records on DUF tapes processed during month.
BI-1-03	Metric Not in Use in Verizon North	
BI-1-04	Metric Not in Use in Verizon North	

Function:		
BI-2 Timeliness of Carrier Bill		
Definition:		
The percent of carrier bills sent to the carrier, unless the CLEC requests special treatment, within 10 business days of the bill date. The bill date is the end of the billing period for recurring, non-recurring and usage charges.		
Exclusions:		
Verizon Test Orders		
Formula:		
(Number of Bills sent within 10 business days divided by Number of Bills sent) multiplied by 100.		
Performance Standard:		
98% in 10 Business Days		
Report Dimensions		
Company:		Geography:
<ul style="list-style-type: none"> CLEC Aggregate 		<ul style="list-style-type: none"> New York
Sub-Metrics		
BI-2-01	Timeliness of Carrier Bill	
Calculation	Numerator	Denominator
	Number of carrier bills sent to CLEC ²⁴ within 10 business days of bill date.	Number of Carrier Bills distributed.

²⁴ Sent to Carrier, unless other arrangements are made with CLEC

Function:		
BI – 3 Billing Accuracy & Claims Processing		
Definition:		
<ul style="list-style-type: none"> These sub-metrics measure the promptness with which Verizon acknowledges and resolves CLEC billing adjustment claims. (Note specific content of acknowledgement and resolution statement to be discussed at an operational meeting date TBD). Business hours for receipt of billing claims are Monday through Friday, 8:00AM until 5:00PM, excluding Verizon legal holidays; CLEC billing adjustment claims received outside these business hours shall be considered received at 8:00AM on the first business day thereafter. Day of receipt shall be considered Day zero (0) for computing acknowledgement performance. Day of acknowledgement of a billing claim is considered Day zero (0) for computing resolution performance. 		
Exclusions:		
<ul style="list-style-type: none"> CLEC claims for adjustments such as: charges for directories, incentive regulation credits, credits for performance remedies, out-of-service credits, and special promotional credits. 		
Performance Standard:		
BI-3-04: 95% within two (2) business daysBI-3-05: 95% within 28 calendar days (after acknowledgement).		
Report Dimensions		
Company: <ul style="list-style-type: none"> CLEC Aggregate 		Geography: <ul style="list-style-type: none"> New York
		These sub-metrics are reported at a state specific level.
Sub-Metrics		
BI-3-01 through BI-3-03	Metrics not in use in Verizon North	
BI-3-04	% CLEC Billing Claims Acknowledged within two (2) Business Days	
Calculation	Numerator	Denominator
	Number of billing claims acknowledged during the month within two business days.	Total number of valid/complete billing adjustment claims acknowledged during the month.
BI-3-05	% CLEC Billing Claims Resolved within 28 Calendar Days After Acknowledgement	
Calculation	Numerator	Denominator
	Number of billing adjustment claims during the month resolved within 28 calendar days after acknowledgement.	Total number of billing adjustment claims resolved during the month.

Section 7

Operator Services & Directory Assistance

(OD)

	Function	<u>Number of Sub-metrics</u>
OD-1	Operator Services/Directory Assistance – Speed of Answer	2
OD-2	LIDB, Routing and OS/DA Platforms	0

Operator Services and Databases (OD)

Function:		
OD-1 Operator Services/Directory Assistance – Speed of Answer		
Performance Standard:		
Standard: Average Speed of Answer provided at parity with Verizon retail.		
Exclusions:		
<ul style="list-style-type: none">None		
Report Dimensions		
For metric OD-1-01 Operator Services – Speed of Answer Company: <ul style="list-style-type: none">New York Retail (and Resale)New York CLEC (facility based and UNE-P)	Geography: <ul style="list-style-type: none">New York	
For metric OD-1-02 Directory Assistance – Speed of Answer <ul style="list-style-type: none">New York Retail (and Resale)New England Operator Service Centers ²⁵		
Sub-Metrics		
OD-1-01	Average Speed of Answer – Operator Services	
Calculation	Numerator	Denominator
	Sum of call answer time from the time the calls enter the queue for an operator to the time the calls are answered by an operator.	Number of Calls Answered.
OD-1-02	Average Speed of Answer – Directory Assistance	
Calculation	Numerator	Denominator
	Sum of call answer time from the time the calls enter the queue for an operator to the time the calls are answered by an operator.	Number of Calls Answered.

²⁵ If no NY CLEC traffic is handled by these centers, the data will not be reported.

Function:
OD-2 LIDB, Routing and OS/DA Platforms
Performance Standard:
<p>LIDB:</p> <ul style="list-style-type: none"> • LIDB reply rate to all query attempts: Bellcore produced standard • LIDB query time out: Bellcore produced standard • Unexpected data values in replies for all LIDB queries: 2% • Group troubles in all LIDB queries Delivery to OS Platform: 2% <p>800 Database: Bellcore produced standard</p> <p>AIN: Bellcore produced standard</p>
Metrics Not Reported:
Verizon New York does not have the capability to report this performance area.

Section 8

General and Miscellaneous Standards

(GE)

Function		<u>Number of Sub-metrics</u>
GE-1	Directory Proofs	0
GE-2	Poles, Ducts, Conduit and Rights of Way	0

General (GE)

Function:
GE-1 Directory Proofs
Performance Standard:
VZ does not provide directory proofs to CLECs. VZ provides Listing Verifications Report 90 days before close out date and provides a Directory Listings view of Listings through the Web-GUI. All business rules are documented in the CLEC and Reseller Handbook.
Metrics Not Reported:
Verizon New York does not have the capability to report this performance area.

Function:
GE-2 Poles, Ducts, Conduit and Rights of Way
Performance Standard:
Verizon New York has specific performance guidelines contained in its pole attachment and conduit license agreements that are consistent with applicable Federal and State requirements. Verizon New York will respond to requests for its engineering records information, and requests for access to its carrying plant in accordance with Verizon's specific performance guidelines.
Metrics Not Reported:
Verizon New York does not have the capability to report this performance area.

Glossary

Application Date	The date that a valid order is received.
ASR	Access Service Request
VZ Administrative Orders	Orders completed by VZ for administrative purposes and NOT at the request of a CLEC or end user. These also include administrative orders for VZ official lines and LIDT (Left in Dial Tone). [SWO<>"NC", "NF"] [CLS<>TOV, or CLS_2<>TOV].
Basic Edits	Front-end edits performed by DCAS prior to order submission. Basic Edits performed against DCAS provided source data include the following validations: State Code must equal NY, CT, MA, ME, NH, VT, RI; CLEC Id can not be blank; All dates and times must be numeric; Order Type must be '1','2','3','4'; Svc Order Type must be '0', '1' '2'; Flowthru Candidate Ind and Flowthru Indicator must be 'Y' or 'N'; Lines Number must be numeric; Service Order Classification must be '0' or '1'; Confirmation Method must be 'E', 'M' 'W'; Each submission must have a unique key (PON + Ver + CLEC Id + State); Confirmation, Reject and Completion Transactions must have matching Submission record. Any changes to basic edits will be provided via VZ Change Control procedures.
BFR	Bona Fide Request Process (BFR): Refer to Appendix D for a summary of the BFR process.
Collocation Milestones	<p>Refer to the state tariff for specific collocation intervals.</p> <p>In Physical Collocation, the CLEC and VZ control various interim milestones they must meet to meet the overall intervals. The interval clock will stop, and the final due date will be adjusted accordingly, for each milestone the CLEC misses (day for day).</p> <p>Prior to the CLEC beginning the installation of its equipment, the CLEC must sign the VZ work completion notice, indicating acceptance of the multiplexing node construction work and providing VZ with a security fee, if required, as set forth in Section 5.5.5. Payment is due within 30 days of bill date. The CLEC may not install any equipment of facilities in the multiplexing node(s) until after the receipt by VZ of the VZ work completion notice and any applicable security fee.</p> <p>In Virtual Collocation, VZ and the CLEC shall work cooperatively to jointly plan the implementation milestones. VZ and the CLEC shall work cooperatively in meeting those milestones and deliverables as determined during the joint planning process. A preliminary schedule will be developed outlining major milestones including anticipated delivery dates for the CLEC-provided transmission equipment and for training.</p>

Change Management Notices	Change Management Notices are notices sent to the CLECs to notify CLECs of scheduled interface-affecting changes.
CLEC Trunk requests	<p>< = 192 Forecasted Trunks are requests for 192 trunks or less that are forecasted by the CLEC and are not projects.</p> <p>> 192 and Unforecasted Trunks are requests that are for greater than 192 trunks, or are not forecasted by the CLEC, or are projects.</p>
Common Final Trunk Blockage:	Common final trunks carry traffic between VZ end offices and the VZ access tandem, including local traffic to VZ customers as well as CLEC customers. (In rare circumstances, it is possible to have a common final trunk group between two end offices.) The percentage of VZ common final trunk groups carrying local traffic, exceeding the applicable blocking design standard (either B.01 or B.005) will be reported. All CLEC trunks are engineered at the B.005 level. In all but the Washington Metropolitan area, local common trunks are engineered at the B.005 level. In the Washington Metropolitan area, common trunks are engineered at the B.01 level.
Common Trunks:	<p>High Usage Trunks carry two-way local traffic between two VZ end offices. High Usage Common Trunks are designed so that traffic will overflow to final trunk groups. Local trunks are designed such that no more than 0.5% (B.005 standard) of traffic will overflow during the busy hour in all Verizon New York geographies.</p> <p>Final Trunks: (All Verizon except New York LATA) Final Trunks carry two-way local and long distance IXC traffic between an end office and an access tandem switch. Common Final Trunks are designed so that no more than 0.5% (B.005 standard) of traffic will block during the busy hour.</p> <p>Final Trunks – Local (NY LATA 132) Final Trunks carry local two-way traffic between an end office and an access tandem switch. Common Final Trunks are designed so that no more than 0.5% (B.005 standard) of traffic will block during the busy hour.</p> <p>Final Trunks – IXC (NY LATA 132 and Washington Metropolitan Calling Area) Final Trunks carry long distance IXC two-way traffic between an end office and an access tandem switch. Common Final Trunks are designed so that no more than 0.5% (B.005 standard) of traffic will block during the busy hour.</p>
Company Initiated Orders	Provisioning orders processed for administrative purposes and not at customer request.
Company Services	Official Verizon Lines
Completion Date	The date noted on the service order as the date that all physical work is completed as ordered.
Coordinated Cut over	A coordinated cut-over is the live manual transfer of a VZ end user to a CLEC completed with manual coordination by VZ and CLEC technicians to minimize disruptions for the end user customer. Also known as a Hot Cut. These all have fixed minimum intervals.
CPE	Customer Premises Equipment.
Cut-Over Window	<p>Amount of time from start to completion of physical cut-over of lines:</p> <p>One (1) to nine (9) lines: one (1) hour</p> <p>10 to 49 lines: two (2) hours</p> <p>50 to 99 lines: three (3) hours</p> <p>100 to 199 lines: four (4) hours</p> <p>200 plus lines: eight (8) hours</p>
DCAS	Direct Customer Access System (DCAS): The system developed initially for the North States (CT, MA, ME, NH, NY, RI and VT) for a CLEC to transact with Verizon. DCAS supports GUI and EDI transactions. Request Manager will

eventually replace DCAS.

Dedicated Final Trunks Blockage:	A dedicated final trunk group does not overflow. Dedicated final trunk groups carry local traffic from a VZ Access Tandem to a CLEC switch. All dedicated final trunk groups to the CLECs are engineered at a design-blocking threshold of B.005.
Dedicated Trunks	<p>High Usage Trunks – CLEC Interconnection: carry one-way traffic from a CLEC end office to a Verizon Tandem Office or carry two-way local traffic between a Verizon end-office and a CLEC end-office. High Usage Common Trunks are designed so that traffic will overflow to final trunk groups. Local trunks are designed such that no more than 0.5% (B.005 standard) of traffic will overflow during the busy hour in all Verizon geographies. These trunks are ordered by the CLEC.</p> <p>Final Trunks – CLEC Interconnection: carry one-way traffic from a CLEC end-office to a Verizon Tandem Office or carry two-way traffic between an end-office and a tandem switch. CLECs order these trunks from VZ and engineer to their desired blocking design threshold.</p> <p>High Usage Trunks – VZ to CLEC Interconnection: carry one-way local traffic from a Verizon end-office to a CLEC end-office. High Usage Common Trunks are designed so that traffic will overflow to final trunk groups. Local trunks are designed such that no more than 0.5% (B.005 standard) of traffic will overflow during the busy hour in all Verizon geographies. VZ orders these trunks from CLECs.</p> <p>Final Trunks – VZ to CLEC Interconnection: carry one-way traffic from a VZ end office or a tandem switch. Final Trunks are designed so that no more than 0.5% (B.005 standard) of traffic will block during the busy hour in all Verizon geographies. VZ orders these trunks from CLECs.</p> <p>High Usage Trunks – IXC Feature Group D: carry two-way traffic between a Verizon end-office and an IXC POP. High Usage Trunks are designed so that traffic will overflow to final trunk groups. IXC trunks are designed such that no more than 0.5% (B.005 standard) of traffic will overflow during the busy hour in all Verizon geographies. IXCs order these trunks from VZ.</p> <p>Final Trunks – IXC Feature Group D; carry two-way traffic between and end-office and a tandem switch. Common Final Trunks are designed so that no more than 0.5% (B.005 standard) of traffic will block during the busy hour in all Verizon geographies. IXCs order these trunks from VZ.</p>
Dispatched Orders:	An order requiring dispatch of a Verizon Field technician outside of a Verizon Central Office. Intervals differ by line size. In all areas, for orders greater than or equal to 10 lines, a facility check is required and the interval negotiated. In many, but not all areas, a facility records check (in Engineering) is also performed for orders with six (6) to nine (9) lines.
Dispatched Troubles:	Loop or Drop Wire Troubles reports found to be in drop wire or outside plant. Disposition codes 03 or 04.
Disposition Codes	The code assigned by the Field Technician upon closure of trouble. This code identifies the plant type/location in the network where the trouble was found.
DUF	Daily Usage Feed:
FOC	Firm Order Confirmation.
Front End Close-Out	A trouble report closed with the customer on the line usually within 10 minutes of receiving the trouble from the customer. These include cancellations by the customer or CLEC. Disposition Codes: 0741(RE<10), 0747, 0706(CP=291).

LIDT	Left in Dial tone Orders. These are orders used after a customer has moved out of a residence dwelling and the line has been disconnected for billing – to leave in reserve Office Equipment (OE) assigned to the cable pair in the Central Office.. Once another customer moves into the location a second order is written to remove the LIDT status to enable the customer order to process. These are not customer-requested orders.
Loop Qualification	Loop qualification is the manual step whereby it is determined if the loop facility meets or can be made to meet specifications necessary for ISDN services or xDSL services.
LSR	Local Service Request
LSRC	Local Service Request Confirmation
Mechanized Flow-Through:	Orders received electronically through the ordering interface (DCAS) and requiring no manual intervention to be entered into the SOP.
Missed Appointment Codes	Verizon Missed Appointment Codes: CB = Business Office, CC = Common Cause, CE = Equipment, CF = Facility, CL = Load (lack of work forces), CS = Switching/programming, CO = Company Other Customer Missed Appointment Codes: SA = Customer Access, SR = Customer Not Ready, SO = Customer Other, SL = Customer requested later due date
Negotiated Intervals	A process whereby Verizon New York and the CLEC discuss and come to a mutual agreement on a delivery date of requested services. This agreement should be based on customer, CLEC and Verizon New York requirements; including but not limited to equipment, facility and work resources required for completing the requested services. Both the CLEC and Verizon New York should be able to explain the requirements and positions for the discussion.
Network Troubles	Troubles with a disposition code of 03 (Drop Wire), 04 (Loop), or 05 (Central Office). Excludes Subsequent reports (additional customer calls while the trouble is pending), Customer Premises Equipment (CPE) troubles, troubles reported but not found on dispatch (Found OK and Test OK), and troubles closed due to customer action.
Non-Mechanized:	Orders that require some manual processing. Includes orders received electronically that are not processed directly into the legacy provisioning systems, and are manually entered by a VZ representative into the VZ Service Order Processor (SOP) system. For orders not received electronically (such as faxed or courier orders), 24 hours are added to all intervals.
No-Dispatch Troubles:	Troubles reports found to be in the Central Office, including frame wiring and translation troubles. Disposition Codes 05.
No-Dispatch Orders:	Orders completed without a dispatch outside a Verizon Central Office. Includes orders with translation changes and dispatches inside a Verizon Central Office.
Orders with ≥ 10 lines:	In some geographic areas, a facility check is completed on orders greater than five (5) lines. In all geographic areas, orders with 10 or greater lines require a facility check prior to order confirmation and due date commitment.
OSS	Operations Support Systems
Parsed CSR	The Parsed CSR transaction returns fielded Customer Service Record data to the customer when the PARSEIND field = Y on the inquiry. The parsed CSR transaction enables CLECs to populate their ordering template. This transaction is available on EDI and CORBA. The Verizon Parsed CRS transaction supports POTS accounts, it currently does not support complex accounts including ISDN and Centrex.
POTS Services	Plain Old Telephone Services (POTS) include all non-designed lines/circuits that originate at a customer's premise and terminate on an OE (switch Office Equipment). POTS include Centrex, basic ISDN and PBX trunks.
PON	Purchase Order Number: Unique purchase order provided by CLEC to VZ placed on LSRC or ASR as an identifier of a unique order.

Projects	<p>Projects are designated by CLECs. For Trunks, any request for a new trunk group, augment for more than 384 trunks, complex (E911 or DA) or request out of the ordinary requiring special coordination, such as rearrangements is considered a project.</p> <p>For Special Services ordered via ASRs the following is considered a project:</p> <p>UNE IOF Projects – New connects: The A or Z end of the circuit must be at the same location, and the number of circuits for DS1 is eight (8) or more circuits, and for DS3 is eight (8) or more circuits.</p> <p>UNE Loop Projects – New connects: The A or Z end of the circuit must be at the same location, and the number of circuits to qualify for a project are : for DS1 = 10 or more circuits, for DS3 10 or more circuits.</p> <p>Coordinated Conversions (when one CLEC assumes another CLECs circuits due to bankruptcy, takeovers or mergers):</p> <p>For additional information on Special Services projects, refer to the CLEC Handbook.</p>
Reject	An order is rejected when there are omissions or errors in required information. Rejects also include queries where notification is provided to a CLEC for clarification on submitted orders. The order is considered rejected and order processing is suspended while a request is returned or queried.
Run Clock	A measure of duration time where no time is excluded. Duration time is calculated comparing the date and time that a trouble is cleared to the date and time that the trouble was reported.
Segment	Segments are parts of whole orders. [NVL SEGMENT, 0=<1] A segment is used to apportion a longer order to meet limitations of record lengths. Similar to a separate page or section on the same order.
SOP	Service Order Processor
Special Services	Any service or element involving circuit design. Any service or element with four wires. Any DS0, DS1 and DS3, no access service. Excludes trunks. IOF and EEL are separately reported for provisioning.
Stop Clock	A measure of duration time where some time is excluded. The clock is stopped when testing is occurring, VZ is awaiting carrier acceptance, or VZ is denied access.
Suspend/Restore Orders	Orders completed by VZ to suspend for non-payment or restore for payment subject to New York PSC Collections guidelines. [SNPRES_IND.IS NOT NULL]
Test Orders	Orders processed for “fictional” CLECs for VZ to test new services, attestation of services etc. Includes the following CLEC AECN’s: ‘DPC’, ‘DPCL’, ‘NYNX’, ‘ZKPM’, ‘ZPSC’, ‘ZTKP’, ‘ZTPS’, ‘ZJIM’.
TGSR	Trunk Group Service Request. A request that CLECs submit to Verizon to request augmentation to the Verizon network to accommodate an increase in CLEC volume.

Two wire digital ISDN Loop	<p>2-Wire unbundled digital loop (previously called 2-Wire Digital Loop) that is compatible with ISDN basic Rate service. It is capable of supporting simultaneous transmission of two (2) B channels and One (1) D channel. It must be provided on non-loaded facilities with less than 1300 OHMs of resistance and not more than 6 kft of bridge tap. This service provides a digital 2-wire enhanced channel. It is equivalent to a 2-wire loop less than 18,000 feet from the NID at the end user's premises to the main distributing frame (which is connected to the CLEC's collocation arrangement), in Verizon's Central Office where the end user is served. The 2-wire digital – ISDN BRI loop, currently offered by Verizon, is designed to support the Integrated Services Digital Network (ISDN) Basic Rate Service which operates digital signals at 160 kilobytes per second (kbps). The 2-wire digital – ISDN BRI loop is only available to the CLEC for use in conjunction with the provision of local exchange service and exchange access to its end-users.</p>
----------------------------	--

Product identification descriptions:

Retail	Major Customer Name/Number entered on Provisioning order first four (4) characters does not contain the values "RSID" which indicates resold or "AECN" which indicates unbundled.
Resale	Major Customer Name/Number entered on Provisioning order-first four (4) characters does contain the value "RSID" the 6th through 10th indicate reseller id. RSID except test and training RSID orders <u>Ordering:</u> ORDER-TYPE of ORDERING-MASTER-REC = ' 1'
UNE	Major Customer Name/Number entered on provisioning order- first four (4) characters contains the values "AECN" which indicates unbundled. Characters 6 through 10 indicate the Telecommunications carrier id. <u>Ordering:</u> ORDER-TYPE of ORDERING-MASTER-REC = '2' or '3'
POTS - Total	Two-wire analog service with a telephone number and POTS class of service. Includes analog loop (SVGAL). <u>Ordering:</u> <ul style="list-style-type: none"> • Service order classification of ordering master rec = 0 <u>Provisioning:</u> <ul style="list-style-type: none"> • Pots Orders are defined as not having a circuit layout (CL_FID IS NULL) or are not for ISDN service (SCM_2 IS NULL) <u>Maintenance:</u> <ul style="list-style-type: none"> • Class Service = 04/05/06/07/08/09/10/13/19/20/21
Complex:	<u>Provisioning:</u> <ul style="list-style-type: none"> • ISDN Basic Rate: Secondary Service Code Modifier (SCM_2) is not blank • ISDN Primary: Service Code Modifier (SCM) begins with "IB" • 2-Wire Digital Services • 2-Wire xDSL Services

Special Services	<p>Special Services are services that require engineering design intervention. These include such services as: high capacity services (DS1 or DS3), Primary rate ISDN, 4 wire xDSL Services, digital services and private lines or foreign served services (a line physically in one exchange, served by another through a circuit).</p> <p>Ordering:</p> <ul style="list-style-type: none"> • Service order classification of ordering master rec = 1 <p>Provisioning:</p> <ul style="list-style-type: none"> • CL_FID is not NULL <p>Maintenance:</p> <ul style="list-style-type: none"> • Criteria for inclusion is Circuit format (cfmt) is 's','t','2','3' as defined by Bellcore standard, report category (rpt_cat) is "CR" indicating a Customer Reported trouble, circuit format does not indicate (fourth character of circuit id for a length of 2) "TK","IB","DI","DO" because these are considered POTS, 7th character of circuit id does not indicate official Verizon line as defined by Bellcore standard practice, trouble code (trbl_cd) is either "FAC" or "CO" indicating the trouble was found in the Facility-cable (from Central Office to customers location), or in the Central Office (the trouble was found within the Verizon Central Office), Maintenance center (MCTR) is not training or blank which excludes troubles entered for employee training purposes, Subsequent calls on the same trouble are not included in these metrics, Troubles are excluded where circuit id (cktid character 4 for a length of 2) indicates non-UNE access tariff filing.
For Trunks:	<p>For Maintenance: Criteria for inclusion is Circuit format (cfmt) is 'M' as defined by Bellcore standard, report category (rpt_cat) is "CR" indicating a Customer Reported trouble, trouble code (trbl_cd) is either "FAC" or "CO" indicating the trouble was found in the Facility-cable (from Central Office to customers location) or in the Central Office (the trouble was found within the Verizon Central Office), Maintenance Center (MCTR) is not training or blank which excludes troubles entered for employee training purposes, Subsequent calls on the same trouble are not included in these metrics.</p>

APPENDIX A

Specials and Trunk Maintenance Code Descriptions

Trunk Maintenance:

Included are all Message Trunk troubles reported by the customer that were caused by a problem within the Verizon network. This does not include troubles for (Special Access) circuits under the Access tariff.

Criteria for inclusion is Circuit format (cfmt) is 'M' as defined by Bellcore standard, report category (rpt_cat) is "CR" indicating a Customer Reported trouble, trouble code (trbl_cd) is either "FAC" or "CO" indicating the trouble was found in the Facility-cable (from Central Office to customers location) or in the Central Office (the trouble was found within the Verizon central office), Maintenance center (MCTR) is not training or blank which excludes troubles entered for employee training purposes, Subsequent calls on the same trouble are not included in these metrics.

Measure Trunks:	criteria
total lines	Count of all Message Trunks that are currently working...i.e. provisioning work is complete.
total network troubles	trouble close out code indicates the trouble was found in the facility or central office part of the Verizon Network - trbl_cd is "FAC" or "CO".
Network trouble report rate	total network troubles divided by total working lines then multiply by 100
mean time to repair	average (mean) of all duration times for receipt of the trouble within the Verizon Operating Support System to the time the circuit was restored to service to the customeravg(actual_dur)the actual_dur field does not contain any time where the Verizon technician could not gain access to the customer location.
out of service	This is used as the divisor for all of the out of service metrics.....upon initial contact with the customer it is determined that the circuit is completely out of service and not just intermittent problem (osi = 'y') and that the trouble completion code indicated that a trouble was found within the Verizon network (trbl_cd is "FAC" or "CO")
out of service over 24	The trouble report entry indicated that the circuit was out of service (osi is 'y') to the customer and that the trouble was reported more than 24hours before it was resolved (actual_dur is > 1440 minutes or 24 hrs) and that the trouble close out code indicates that a trouble was found within the Verizon Facility or Central office network (trbl_cd is "FAC" or "CO").
% out of service over 24	total troubles out of service more than 24 hours divided by total troubles that were out of service to the customer then multiply by 100

repeats	Total troubles entered - where a previous trouble report on the same circuit occurred within the previous 30 days. Trouble is scored as a "repeat". Count of all repeats (rpr_flag is 'y') where trouble close out code indicates trouble was found within the Verizon Network.
% repeats	Total repeated troubles divided by total troubles...then multiply by 100.

Trunks:

trouble code	the code that identifies the type of trouble found
Repeat	The flag indicates that this trouble report was received within 30 days of the restoral date of the last trouble reported on the circuit.
out of service indicator	The flag is set to 'y' if the circuit was out of service when the report was taken, or was scored as out of service during the life of the trouble. For designed circuits the flag is always set to y

Specials Services Maintenance:

Included are all special service troubles reported by the customer that were caused by a problem within the Verizon network. This does not include troubles for special access circuits under the Access tariff.

Criteria for inclusion is Circuit format (cfmt) is 's','t','2','3' as defined by Bellcore standard, report category (rpt_cat) is "CR" indicating a Customer Reported trouble, circuit format does not indicate (fourth character of circuit id for a length of 2) "TK","IB","DI","DO" because these are considered POTS, 7th character of circuit id does not indicate official Verizon line as defined by Bellcore standard practice, trouble code (trbl_cd) is either "FAC" or "CO" indicating the trouble was found in the Facility-cable (from Central Office to customers location) or in the Central Office (the trouble was found within the Verizon central office), Maintenance center (MCTR) is not training or blank which excludes troubles entered for employee training purposes, Subsequent calls on the same trouble are not included in these metrics, Troubles are excluded where circuit id (cktid character 4 for a length of 2) indicates access tariff filing. table will be provided.

Measure Special Services:	Criteria
total lines	count circuits where center (MCTR) is not blank, not an official service (cktid 8,1) is not z (lines are in a different data base than specials and the circuit id field has a different layout),and only count 1 end of a point to point circuit (CKLEND='z') z indicates customer location.
total network troubles	trouble close out code indicates the trouble was found in the facility or central office piece of the special services circuit - trbl_cd is "FAC" or "CO" .
Network trouble report rate	total network troubles divided by total working lines then multiply by 100.
total troubles loop	trouble close out code indicates the trouble was found in the facility portion of the Verizon Network - (trbl_cd is "FAC")

Appendix A
Maintenance Additional details
Continued

network trouble report rate- loop	total troubles loop divided by total lines multiply by 100
total troubles "CO"	trouble close out code indicates the trouble was found in the central office portion of the Verizon Network - (trbl_cd is "CO").
network trouble report rate - co	total troubles central office divided by total lines then multiply by 100.
mean time to repair	Average (mean) of all duration times for receipt of the trouble within the Verizon Operating Support System to the time the circuit was restored to service to the customeravg(actual_dur)the actual_dur field does not contain any time where the Verizon technician could not gain access to the customer location.

Special Services:

mean time to repair loop	average (mean) of all duration times for receipt of the loop trouble within the Verizon Operating Support System to the time the circuit was restored to service to the customeravg(actual_dur) and trbl_cd is "FAC"....the actual_dur field does not contain any time where the Verizon technician could not gain access to customer location
mean time to repair co	average (mean) of all duration times from receipt of the CO trouble within the Verizon Operating Support System to the time the circuit was restored to service to the customer ...avg(actual_dur) and trbl_cd is "CO"....the actual_dur field does not contain any time where the Verizon Technician could not gain access to the customer location or the customer was verifying the status of the circuit.
out of service	This is used as the divisor for all of the out of service metrics.....upon initial contact with the customer it is determined that the circuit is completely out of service and not just intermittent problem (osi = 'y') and that the trouble completion code indicated that a trouble was found within the Verizon network (trbl_cd is "FAC" or "CO").
out of service loop	This is used as the divisor for all of the loop out of service metrics.....upon initial contact with the customer it is determined that the circuit is completely out of service and not just intermittent problem (osi = 'y') and that the trouble completion code indicated a trouble was found within the LOOP piece of the Verizon network (trbl_cd is "FAC").
out of service co	This is used as the divisor for all of the CO out of service metrics.....upon initial contact with the customer it is determined that the circuit is completely out of service and not just intermittent problem (osi = 'y') and that the trouble completion code indicated that a trouble was found within the CO piece of the Verizon network (trbl_cd is "CO").

Appendix A
Maintenance Additional details
Continued

out of service over 24	The trouble report entry indicated that the circuit was out of service (osi is 'y') to the customer and that the trouble was reported more than 24hours before it was resolved (actual_dur is > 1440 minutes or 24 hrs) and that the trouble close out code indicates that a trouble was found within the Verizon Facility or Central office network (trbl_cd is "FAC" or "CO").
% out of service over 24	total troubles out of service more than 24 hours divided by total troubles that were out of service to the customer then multiply by 100.
out of service over 24- loop	The trouble report entry indicated that the circuit was out of service (osi is 'y') to the customer and that the trouble was reported more than 24hours before it was resolved (actual_dur is > 1440 minutes or 24 hrs) and that the trouble close out code indicates that a trouble was found within the Verizon Facility network (trbl_cd is "FAC").
% out of service over 24 loop	total troubles out of service more than 24 hours loop divided by total troubles that were out of service - loop to the customer then multiply by 100.
out of service over 24- CO	The trouble report entry indicated that the circuit was out of service (osi is 'y') to the customer and that the trouble was reported more than 24hours before it was resolved (actual_dur is > 1440 minutes or 24 hrs) and that the trouble close out code indicates that a trouble was found within the Verizon Central Office network (trbl_cd is "CO").
% out of service over 24 CO	total troubles out of service more than 24 hours CO divided by total troubles that were out of service - CO to the customer then multiply by 100.
repeats	total troubles entered - where a previous trouble report on the same circuit occurred within the previous 30 days. Trouble is scored as a "repeat". Count of all repeats (rpr_flag is 'y') where trouble close out code indicates trouble was found within the Verizon Network.
% repeats	Total repeated troubles divided by total troubles...then multiply by 100.
trouble code	the code that identifies the type of trouble found
Repeat	The flag indicates that this trouble report was received within 30 days of the restoral date of the last trouble reported on the circuit.
out of service indicator	The flag is set to 'y' if the circuit was out of service when the report was taken, or was scored as out of service during the life of the trouble. For designed circuits the flag is always set to y

Example of Actual coding for Out of Service Specials:

stop oos le 3 (5)	actual_dur is le 003:00 (hrs/min) and osi is y and trbl_cd is co
% stop oos le3(5)	stop oos le 3(5) / total oos 5 * 100
stop oos le 4(5)	actual_dur is le 004:00 (hrs/min) and osi is y and trbl_cd is co
% stop oos le 4(5)	stop oos le 4(5) / total oos 5 * 100
stop oos le 4 (3,4)	actual_dur is le 004:00 (hrs/min) and osi is y and trbl_cd is fac
% stop oos le4(3,4)	stop oos le 4(3,4) / total oos 3/4 * 100
stop oos le 16(3,4)	actual_dur is le 016:00 (hrs/min) and osi is y and trbl_cd is fac
% stop oos le 16(3,4)	stop oos le 16(3,4) / total oos 3/4 * 100

APPENDIX B

SORD Code Tables: (Service Order Database Codes)

ORDER TYPE:

Defines what type of service is requested

N	New Service
T	The "To" portion when a customer moves From one address To another address
C	Change request to existing service (add or remove features/services)

Appointment Type Code (ATC):

This code identifies how the appointment date was derived

W	The customer accepted the company's offered due date
X	The customer requested a due date that was greater than the company's offered Due date
S	The customer requested a due date that was earlier than the companies offered due date
C	The customer requested a special due date to coordinate a hot cut.
R	A due date could not be applied due to company or customer reasons.

Missed Appointment Code (MAC):

When the original scheduled due date is missed a code is applied to the order to identify the reason for the miss

Customer Missed Appointment:

SA	Access could not be obtained to the customers premises(customer not at home)
SR	Customer was not ready to receive the new service
SO	Any other customer caused reason for the delay (e.g., unsafe working conditions at the customer site)
SL	Customer requested a later appointment date prior to the due date
SP	Customer requested an earlier appointment date prior to the due date
—	Under Development: CLEC Not Ready
—	Under Development: CLEC Not Ready – due to late FOC

Company (VZ) Missed Appointment:

CA	The cable pair from the VZ central office to the customer premises could not be Assigned by the due date due to any reason, including assignment load. If after the due date it is determined that no facilities were available, a CF miss is applied.
CB	The VZ business office taking the request caused the delay (misplaced the order)
CC	A Common Cause that affected a large area caused the delay (Hurricanes/work stoppages)
CF	The assigned cable facility was bad
CL	Not enough VZ technicians to complete the work on a given day
CO	Any other delay caused by the Company not listed here (e.g., Technicians truck broke down)
CS	The VZ Central office work was not complete (line not programmed)

SWO:

A code applied when the order is completed to identify the service grouping

NR	Residence service
NL	Small business (2 lines or less)
NV	Large business (3 lines or more)
NF & NC	Internal VZ service
NS	Special services
NP	VZ Coin services
NI	Private Public Pay Phone (not VZ)